

Isobar 280 CO Rock X-HP



Product group	110
Cover design	Wrapped
Color	Black
Cover tube resistance	Abrasion, Oil, Weather
Inner tube resistance	Oil
Safety factor	1:4
Bundled pipes/hoses	1
Max temperature (°C)	121
Reinforcement layers	4
Reinforcement mtrls	Steel wire
Min temperature (°C)	-40

A very flexible spiral hose for the toughest applications. With the extremely durable cover and flexibility the hose is suited in applications with high demands for high flow and high pressure and is easy to assemble. MSHA approved. Exceeds the requirements of SAE 100 R13. Comes in 15,2 meter rolls. Sample ferrule: 4400-09-xx (use only with 3/4" - 1") 4400-13-xx (use only with 1 1/4" - 1 1/2") 4700-04-xx (use only with 3/4" and 1") 4700-09-xx (use only with 3/4" and 1") 4700-10-xx (use only with 1 1/4" and 1 1/2")

Part no	ID (inch)	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	Weight (kg)
10208408	1/2"	13	23.8	27.5	89	0.7
10208412	3/4"	19	30.9	27.5	121	1.2
10208416	1"	25	38.2	27.5	153	1.8

