

P.T.F.E. HOSE



Product group	110
Cover design	Wrapped
Color	Silver
Media description	Chemicals, Oil, Water
Safety factor	1:4
Bundled pipes/hoses	1
Inner tube material	PTFE
Max temperature (°C)	260
Reinforcement layers	1
Reinforcement mtrls	Steel spiral
Min temperature (°C)	-60

A very suitable hose for hazardous environments together with dissolvents, paint, hydraulic oils, food as well as other applications where high temperature, high pressure and resistance towards chemicals are needed along with elastic characteristics. Age resistant.
Ferrule: 4200-26-xx

Part no	ID (inch)	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	Weight (kg)
10920102	1/8"	3.35	6.27	22.5	40	0.06
10920103	3/16"	4.83	7.87	19	50	0.08
10920104	1/4"	6.48	9.27	18	75	0.11
10920105	5/16"	8	11.18	17.5	100	0.15
10920106	3/8"	9.65	12.45	16.5	125	0.16
10920108	1/2"	12.83	16	12	165	0.22
10920110	5/8"	16	19.3	8.8	200	0.29
10920112	3/4"	19.18	22.86	7	230	0.38
10920116	1"	25.53	29.46	6	300	0.5

