

Egefex 2 CO



Product group	100
Cover design	Wrapped
Color	Black
Cover tube resistance	Abrasion, Heat, Weather,
Inner tube resistance	Oil
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube material	Synthetic rubber
Inner tube material	Synthetic rubber
Max temperature (°C)	100
Reinforcement layers	2
Reinforcement mtrls	Steel wire
Min temperature (°C)	-40

A hose for applications with medium to high pressures and a lot of external abrasion. Equivalent to EN 853 2SN. DNV-, MED- and MSHA-approved. The certificates refer to dimensions 3/16" - 1". Part numbers ending with 30 are sold on Bobin.

Part no	ID (inch)	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	Weight (kg)
11021404	1/4"	6.5	15	40	100	0.31
1102140430	1/4"	6.5	15	40	100	0.31
11021405	5/16"	8	16.6	35	115	0.39
1102140530	5/16"	8	16.6	35	115	0.39
11021406	3/8"	10	19	33	130	0.46
1102140630	3/8"	10	19	33	130	0.46
1102140830	1/2"	13	22.2	27.5	180	0.55
11021410	5/8"	16	25.4	25	200	0.67
11021412	3/4"	19	29.3	21.5	240	0.84
11021416	1"	25	38.1	16.5	300	1.24
11021420	1 1/4"	32	48.3	12.5	420	1.8
11021424	1 1/2"	38	54.6	9	500	2.18
11021432	2"	51	67	8	630	2.81

