

# EGEFLEX 2 HT



|                              |                  |
|------------------------------|------------------|
| <b>Product group</b>         | 100              |
| <b>Color</b>                 | Blue             |
| <b>Cover design</b>          | Wrapped          |
| <b>Safety factor</b>         | 1:4              |
| <b>Bundled pipes/hoses</b>   | 1                |
| <b>Cover tube resistance</b> | Oil, Weather     |
| <b>Inner tube resistance</b> | Oil              |
| <b>Cover tube material</b>   | Synthetic rubber |
| <b>Inner tube material</b>   | Synthetic rubber |
| <b>Max temperature (°C)</b>  | 150              |
| <b>Reinforcement layers</b>  | 2                |
| <b>Reinforcement mtrls</b>   | Steel wire       |
| <b>Min temperature (°C)</b>  | -40              |

The hose is suitable for high pressure lines for oil, fuel or lubrication systems with extra high temperature. Equivalent to EN 853 2SN.

| Part no  | Working pressure (MPa) | Bend radius (mm) | ID (inch) | ID (mm) | OD (mm) | Weight (kg) |
|----------|------------------------|------------------|-----------|---------|---------|-------------|
| 11025010 | 22.7                   | 200              | 5/8"      | 16      | 25.2    | 0.8         |
| 11025012 | 21                     | 240              | 3/4"      | 19      | 29.5    | 1           |
| 11025016 | 17.5                   | 300              | 1"        | 25      | 37.9    | 1.44        |
| 11025020 | 15.7                   | 420              | 1 1/4"    | 32      | 48.8    | 2.39        |
| 11025024 | 12.2                   | 500              | 1 1/2"    | 38      | 54.6    | 2.6         |
| 11025032 | 10.5                   | 630              | 2"        | 51      | 67.8    | 3.38        |

