

Kappaflex 2 CO Smooth



Product group	100
Color	Green
Cover design	Smooth
Inner tube resistance	Oil
Media description	Oil
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	Abrasion, Oil, Ozone
Cover tube material	Synthetic rubber
Inner tube material	Synthetic rubber
Max temperature (°C)	100
Reinforcement layers	2
Reinforcement mtrls	Steel wire
Min temperature (°C)	-40

A hose for applications with medium to high pressures and a lot of external abrasion. Exceeds the requirements of EN857 2SC (42.5 - 21.0 MPa Part numbers ending with *30 are delivered on coil.

Part no	OD (mm)	Working pressure (MPa)	Bend radius (mm)	ID (inch)	ID (mm)	Weight (kg)
1104170430	13.4	42.5	75	1/4"	6.5	0.29
11041705	15	40	85	5/16"	8	0.34
11041706	17.2	35	90	3/8"	10	0.42
11041708	20.4	31	130	1/2"	13	0.58
1104170830	20.4	31	130	1/2"	13	0.58
11041710	23.9	28	160	5/8"	16	0.7
1104171230	27.7	28	195	3/4"	19	0.82
11041716	35.4	21	250	1"	25	1.19

