Kappaflex 2K CO Rock



Product group	100
Color	Black
Cover design	Wrapped
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	Abrasion, Oil, Weather
Inner tube resistance	Oil
Media description	Oil
Cover tube material	Synthetic rubber
Inner tube material	Synthetic rubber
Max temperature (°C)	100
Reinforcement layers	2
Reinforcement mtrls	Steel wire
Min temperature (°C)	-50

Ozone resistant hose for applications with high pressures and high abrasion. Well suited for marine applications. Impulse tested up to one million cycles. (1 1/4" to 200 000 cycles). Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved.

Part no	Working pressure (MPa)	Bend radius (mm)	ID (inch)	ID (mm)	OD (mm)	Weight (kg)
11056304	45	45	1/4"	6.5	13.4	0.27
1105630430	45	45	1/4"	6.5	13.4	0.27
11056305	42	60	5/16"	8	15	0.32
1105630530	42	60	5/16"	8	15	0.32
11056306	38.5	70	3/8"	10	17.4	0.38
1105630630	38.5	70	3/8"	10	17.4	0.38
11056308	34.5	90	1/2"	13	20.6	0.53
1105630830	34.5	90	1/2"	13	20.6	0.53
11056310	29	130	5/8"	16	23.6	0.66
11056312	28	160	3/4"	19	27.7	0.87
11056316	20	210	1"	25	35.6	1.17
11056320	17.5	300	1 1/4"	32	43.5	1.59



HYDROSCAND