

INDUSTRIAL COOLING HOSE, FIBERGLASS



Product group	140
Color	White
Media description	Water
Safety factor	1:3
Bundled pipes/hoses	1
Cover tube material	EPDM
Flat coil	No
Inner tube material	EPDM
Antstatic wire	No
Max temperature (°C)	120
Reinforcement layers	No extra reinforcement
Reinforcement mtrls	Textile
Min temperature (°C)	-30

Used as a protection and cooling hose where the working temperature is high, e.g. melting furnaces and foundries. The cover cord is made of fiberglass, which gives the hose a good resistance towards flames. Sustains 530° C temporary radiation as well as glowing steel spatter.

Part no	Working pressure (MPa)	ID (mm)	Length metre per coil	OD (mm)	Bend radius (mm)	Weight (kg)
14020008	1.2	13	40	29	50	0.44
14020010	1.2	16	40	32	85	0.77
14020012	1.2	19	40	35	95	0.69
14020016	1.2	25	40	41	125	0.73
14020020	1.2	32	40	48	160	0.88
14020024	1.2	38	40	55	380	1.1
14020026	1.2	40	40	57	400	1.9
14020030	1.2	45	40	63	450	2.1
14020032	1.2	51	40	71	250	2.24
14020040	1.2	63.5	40	81	630	2.91
14020048	1.2	76	40	96	380	3.3

