

AQUASEWER, FLUSHING HOSE 250 BAR



Product group	140
Color	Black
Cover design	Smooth
Cover tube resistance	Abrasion, Weather
Media description	Water
Safety factor	1:2.5
Bundled pipes/hoses	1
Cover tube material	NR/BR
Flat coil	No
Inner tube material	SBR
Antstatic wire	No
Max temperature (°C)	80
Reinforcement layers	2
Reinforcement mtrls	Textile
Min temperature (°C)	-35

A hose for high pressure flushing of sewers and sewage systems. Its abrasion proof cover and textile reinforcement make it flexible and very easy to handle. Pre-assembled with an internal, alternative external, and external thread (BSP). Delivered with Pressure Test Certificate.

Part no	Thread 1	Thread 2	ID (mm)	Length metre per coil	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
14150608	Female	Male	13	60	25	70	25	0.46
1415060890	Male	Male	13	60	25	70	25	0.46
14150808	Female	Male	13	80	25	70	25	0.46
1415080890	Male	Male	13	80	25	70	25	0.46
14151208	Female	Male	13	120	25	70	25	0.46
1415120890	Male	Male	13	120	25	70	25	0.46
14151216	Female	Male	25	120	39	110	25	0.87
14151220	Female	Male	32	120	48	150	25	1.28