Universal PU hose, 20 Bar

| Product group | 140 | | |
|-----------------------------|--|--|--|
| Color | Green | | |
| Cover design | Smooth | | |
| Bundled pipes/hoses | 1 | | |
| Media description | Air pressur <mark>e</mark> , Ai <mark>r 🔤</mark> | | |
| Safety factor | 1:3 | | |
| Antstatic wire | No | | |
| Cover tube material | PVC/NBR | | |
| Flat coil | No | | |
| Inner tube material | PVC | | |
| Max temperature (°C) | 60 | | |
| Reinforcement layers | No extra reinforcement | | |
| Reinforcement mtrls | Textile | | |
| Min temperature (°C) | -15 | | |
| | Color Cover design Bundled pipes/hoses Media description Safety factor Antstatic wire Cover tube material Flat coil Inner tube material Max temperature (°C) Reinforcement layers Reinforcement mtrls | | |

A very light hose, only 2/3 of a conventional PVC or rubber hose. It is very flexible and has a high ozone resistance. It is also resistant towards lubricates, oils and non-aggressive chemicals. Well suited for pneumatic tools and sandblasting. Food quality.

| Part no | Bend radius (mm) | Working pressure (MPa) | ID (mm) | Length metre per coil | OD (mm) | Weight (kg) |
|----------|------------------|------------------------|---------|-----------------------|---------|-------------|
| 14243004 | 20 | 2 | 6 | 100 | 10 | 0.07 |
| 14243006 | 38 | 2 | 10 | 50 | 15 | 0.13 |
| 14243008 | 55 | 2 | 13 | 30 | 19 | 0.2 |



