

# Yachtoil SW, marine fuel hose, ISO 7840



<b>Product group</b>	140
<b>Color</b>	Black
<b>Cover design</b>	Smooth
<b>Media description</b>	Oil and gasoline
<b>Bundled pipes/hoses</b>	1
<b>Cover tube resistance</b>	Flame resistant, Oil, Weather
<b>Antstatic wire</b>	No
<b>Cover tube material</b>	CR
<b>Flat coil</b>	No
<b>Inner tube material</b>	NBR
<b>Max temperature (°C)</b>	80
<b>Reinforcement layers</b>	1
<b>Reinforcement mtrls</b>	Textile
<b>Min temperature (°C)</b>	-35

A very flexible fuel hose that is resistant to gasoline, unleaded gasoline and diesel. The hose is manufactured according to SS-EN ISO 7840 A1 regarding flame resistance and permeability. This means that it can sustain 2,5 minutes in open fire without leaking. For larger dimensions, see 1432-31.

Part no	OD (mm)	Bend radius (mm)	Burst pressure (MPa)	Working pressure (MPa)	ID (mm)	Length metre per coil	Weight (kg)
14323002	14.5	25	3	1	4	50	0.23
14323003	12.5	50	3	1	5	50	0.15
14323004	13.5	60	3	1	6	50	0.17
14323005	16.5	80	3	1	8	50	0.24
14323006	18.5	100	3	1	10	50	0.28
14323008	22.5	130	3	1	13	50	0.4
14323010	25.5	160	3	1	16	50	0.46

