

# Yachtoil SW, marine fuel hose, ISO 7840



<b>Product group</b>	140
<b>Color</b>	Black
<b>Cover design</b>	Wrapped
<b>Media description</b>	Oil and gasoline
<b>Safety factor</b>	1:3
<b>Bundled pipes/hoses</b>	1
<b>Cover tube resistance</b>	Flame resistant, Oil, Weather
<b>Antstatic wire</b>	No
<b>Cover tube material</b>	CR
<b>Flat coil</b>	No
<b>Inner tube material</b>	NBR
<b>Certificate</b>	CE, RINA
<b>Max temperature (°C)</b>	80
<b>Reinforcement layers</b>	2
<b>Reinforcement mtrls</b>	Textile
<b>Min temperature (°C)</b>	-20

This hose is manufactured according to SS-EN ISO 7840 A1 regarding flame resistance and permeability. This means that it can sustain 2,5 minutes in open fire without leaking. It is used as a fuel refill hose on smaller boats.

Part no	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Length metre per coil	Weight (kg)
14323112	32	120	0.25	19	40	0.64
14323124	50	190	0.5	38	61	1.24
14323138	67	305	0.5	55	61	-
14323148	88	760	0.25	76	20	2.1

