HYDROSCAND MULTIFLEX SUCTION AND PRESSURE



Product group	140
Color	Black
Cover design	Corrugated
Safety factor	1:3
Bundled pipes/hoses	1
Cover tube resistance	Abrasion, Oil, Weather
Inner tube resistance	Oil
Media description	Oil and gasoline
Antstatic wire	No
Cover tube material	CR
Flat coil	No
Inner tube material	Synthetic rubber
Max temperature (°C)	120
Reinforcement layers	1
Reinforcement mtrls	Steel wire, Textile
Min temperature (°C)	-30

Suction and pressure hose for oil and gasoline with no more than 50% aromatic contents. The hose is corrugated which is a very good solution where there is a need for a flexible hose.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length metre per coil	OD (mm)	Weight (kg)
14386008	40	0.5	13	50	20	22	0.32
14386010	45	0.5	16	50	20	24	0.39
14386012	50	0.5	19	50	20	27	0.43
14386014	60	0.5	22	50	20	31	0.49
14386016	65	0.5	25	50	20	34	0.55
14386018	75	0.5	28	50	20	35	0.59
14386020	80	0.5	32	50	20	41	0.65
14386022	90	0.5	35	50	20	43	0.7
14386024	100	0.5	38	50	20	46	0.74
14386026	115	0.5	42	50	20	50	0.8
14386030	125	0.5	45	50	20	53	0.86
14386032	145	0.5	51	80	20	60	1
14386036	160	0.5	58	50	20	66	1.38
14386040	180	0.5	63.5	50	20	72	1.52



Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length metre per coil	OD (mm)	Weight (kg)
14386044	210	0.5	70	50	20	79	1.75
14386048	230	0.5	76	50	20	85	1.99
14386064	330	0.5	102	50	20	114	2.72
14386080	330	0.5	127	50	20	144	4.08

