

# WATER HOSE, 10 BAR



|                             |                        |
|-----------------------------|------------------------|
| <b>Product group</b>        | 140                    |
| <b>Cover design</b>         | Smooth                 |
| <b>Color</b>                | White                  |
| <b>Media description</b>    | Water                  |
| <b>Safety factor</b>        | 1:2.2                  |
| <b>Bundled pipes/hoses</b>  | 1                      |
| <b>Cover tube material</b>  | PVC                    |
| <b>Flat coil</b>            | No                     |
| <b>Inner tube material</b>  | PVC                    |
| <b>Antstatic wire</b>       | No                     |
| <b>Max temperature (°C)</b> | 60                     |
| <b>Reinforcement layers</b> | No extra reinforcement |
| <b>Reinforcement mtrls</b>  | Textile                |
| <b>Min temperature (°C)</b> | -15                    |

An excellent water hose well suitable for boats and trailers. The cover has good UV-resistance and the inner tube is cadmium free. The design prevents algal bloom in the hose. The hose has a very good bend radius.

| Part no  | Working pressure (MPa) | ID (mm) | Length metre per coil | OD (mm) | Bend radius (mm) | Weight (kg) |
|----------|------------------------|---------|-----------------------|---------|------------------|-------------|
| 14581008 | 1                      | 12.5    | 15                    | 17.8    | 125              | 0.18        |
| 14581010 | 1                      | 15      | 15                    | 20.8    | 150              | 0.2         |