Vacuum hose, Polyurethane



Product group	140
Color	Transparent
Cover design	Corrugated
Media description	Food and beverage, Materials, Ventilation
Bundled pipes/hoses	1
Flat coil	No
Inner tube material	PU
Antstatic wire	No
Cover tube material	PU
Max temperature (°C)	85
Reinforcement layers	No extra reinforcement
Reinforcement mtrls	PVC
Min temperature (°C)	-25

A hose suitable for ventilation; suction of gases, smoke, dust pellets; and for transportation of mineral wool insulation. The hose is internally smooth and very flexible. Also available in antistatic design, see 1463-40-xx. Food approved.

Part no	ID (mm)	Vacuum pr. Max%	Length metre per coil	OD (mm)	Thickness (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
14631016	25	40	20	26.2	0.5	25	0.06	0.19
14631020	32	40	20	33.2	-	32	0.06	0.19
14631024	38	30	20	39.2	-	38	0.04	0.25
14631030	45	30	20	46.2	-	45	0.04	0.32
14631032	50	30	20	51.4	-	50	0.04	0.39
14631039	60	30	20	61.4	-	60	0.04	0.44
14631048	75	30	20	76.4	-	75	0.03	0.6
14631050	80	30	20	81.4	-	80	0.02	0.65
14631055	90	30	20	91.6	-	90	0.02	0.75
14631064	100	30	20	101.6	-	100	0.02	0.85
14631080	125	30	20	126.6	-	125	0.02	1.17
14631096	152	30	20	153.8	-	150	0.01	1.45
14631160	160	30	20	161.8	-	160	0.01	1.7
14631180	180	30	10	181.8	-	180	0.01	2



HYDROSCAND