

HYDROSCAND ARCTIC PVC SUCTION HOSE -40°C



Product group	140
Cover design	Corrugated
Media description	Water
Safety factor	1:3
Bundled pipes/hoses	1
Inner tube material	PVC
Antstatic wire	No
Cover tube material	PVC
Flat coil	No
Max temperature (°C)	45
Reinforcement layers	1
Reinforcement mtrls	PVC
Min temperature (°C)	-40

A suction hose for sewage trucks, grains and fertilizing. Extremely pliable and flexible at very low temperatures. The extra hard PVC spiral provides excellent protection against external abrasion/friction. The hose is oil resistant.

Part no	ID (mm)	Vacuum pr. Max%	Length metre per coil	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
15081032	51	90	30	62	165	0.3	1.1
1508103290	51	90	50	62	165	0.3	1.1
15081048	76	90	30	89	260	0.3	1.8
1508104890	76	90	50	89	260	0.3	1.8
15081056	89	90	30	103	300	0.25	2.25
15081064	102	90	30	117	330	0.2	2.8
1508106490	102	90	50	117	350	0.3	2.8
15081080	127	90	20	144	420	0.1	4
15081096	152	90	20	170	510	0.1	5

