Blue silicon hose



Product group	140
Media description	Water
Safety factor	1:3
Bundled pipes/hoses	1
Inner tube material	Silicon
Antstatic wire	No
Cover tube material	Silicon
Flat coil	No
Max temperature (°C)	180
Min temperature (°C)	-50

Excellent hose for cool and heat systems in buses and trucks. The silicon may come into contact with oil, but should NOT be used as a transporter hose for petroleum products, nor in oil baths.

Part no	Length metre per coil	OD (mm)	Working pressure (MPa)	ID (mm)	Reinforcement layers	Reinforcement mtrls	Weight (kg)
15091004	1	15	0.88	6	No extra reinforcement	Clean	0.31
15091006	1	19	0.83	10	No extra reinforcement	Clean	0.34
15091008	1	21	0.79	13	No extra reinforcement	Clean	0.36
15091010	1	25	0.75	16	No extra reinforcement	Clean	0.43
15091011	1	27	0.67	18	No extra reinforcement	Clean	0.46
15091012	1	28	0.66	19	No extra reinforcement	Clean	0.48
15091014	1	31	0.61	22	No extra reinforcement	Clean	0.54
15091016	1	34	0.58	25	No extra reinforcement	Clean	0.59
15091018	1	37	0.57	28	No extra reinforcement	Clean	0.63
15091019	1	39	0.55	30	No extra reinforcement	Clean	0.68
15091020	1	41	0.53	32	No extra reinforcement	Clean	0.72
15091022	1	44	0.51	35	No extra reinforcement	Clean	0.76
15091024	1	47	0.49	38	No extra reinforcement	Clean	0.79
15091025	1	50	0.48	40	No extra reinforcement	Clean	0.81
15091026	1	49.4	0.4	41	No extra reinforcement	Clean	0.83
15091030	1	54	0.47	45	No extra reinforcement	Clean	0.87
15091031	1	57	0.33	48	No extra reinforcement	Clean	0.95
15091032	1	60	0.37	51	No extra reinforcement	Clean	1.05
15091038	1	65	0.31	55	No extra reinforcement	Clean	1.21



HYDROSCAND

Part no	Length metre per coil	OD (mm)	Working pressure (MPa)	ID (mm)	Reinforcement layers	Reinforcement mtrls	Weight (kg)
15091039	1	70	0.27	60	No extra reinforcement	Clean	1.29
15091040	1	73	0.23	64	No extra reinforcement	Clean	1.35
15091044	1	80	0.22	70	No extra reinforcement	Clean	1.49
15091048	1	86	0.21	76	No extra reinforcement	Clean	1.58
15091051	1	90	0.18	80	No extra reinforcement	Clean	1.66
15091053	1	93	0.17	83	No extra reinforcement	Clean	1.72
15091056	1	100	0.15	89	No extra reinforcement	Clean	1.85
15091064	1	113	0.13	102	No extra reinforcement	Clean	2.32
15091072	1	122.4	0.2	114	No extra reinforcement	Clean	0.1
15091080	1	138	0.11	127	No extra reinforcement	Clean	2.86
15091096	1	163	0.09	152	No extra reinforcement	Clean	3.42



HYDROSCAND