

OIL SUCTION AND PRESSURE HOSE PVC



Product group	140
Color	Blue
Cover design	Slightly corrugated
Media description	Oil, Water
Safety factor	1:3
Bundled pipes/hoses	1
Cover tube material	PVC/NBR
Flat coil	No
Inner tube material	PVC/NBR
Antstatic wire	No
Max temperature (°C)	60
Reinforcement layers	1
Reinforcement mtrls	PVC
Min temperature (°C)	-25

A super elastic oil resistant suction and pressure hose for paraffins, grease oils, mineral based hydraulic oils, diesel, sludge and water etc. Low weight and very flexible. Also available in antistatic design, see 1533-10.

Part no	ID (mm)	Vacuum pr. Max%	Length metre per coil	OD (mm)	Bend radius (mm)	Weight (kg)	Working pressure (MPa)
15330012	19	90	50	26	100	0.36	0.7
15330016	25	90	50	34	115	0.48	0.7
15330020	32	90	50	41	130	0.58	0.6
15330024	38	90	50	48	140	0.67	0.6
15330032	51	90	50	61	200	0.98	0.5
15330040	63	90	50	75	275	1.35	0.5
15330048	76	90	50	88	310	1.7	0.5
15330064	102	80	30	116	410	2.6	0.4