EXHAUST HOSE FOR HOT AIR, NEOPREN, SINGLE COATED



Product group	140
Cover design	Slightly corrugated
Color	Black
Bundled pipes/hoses	1
Media description	Ventilation
Cover tube material	CR
Flat coil	No
Antstatic wire	No
Max temperature (°C)	135
Reinforcement layers	1
Reinforcement mtrls	Steel spiral
Min temperature (°C)	-35

A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and very flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

Part no	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length metre per coil	Bend radius (mm)	Weight (kg)
15610016	0.15	25	5	4	17	0.12
15610020	0.15	32	5	4	19	0.16
15610029	0.15	44	4	4	26	0.21
15610032	0.15	51	4	4	30	0.25
15610040	0.13	63	4	4	36	0.31
15610048	0.11	76	3	4	42	0.42
15610055	0.11	89	3	4	49	0.5
15610064	0.11	102	2	4	55	0.56
15610080	0.09	127	2	4	69	0.8
15610096	0.08	152	1	4	81	1.04
15610180	0.06	180	1	4	94	1.21
15610203	0.06	203	1	4	107	1.39
15610254	0.04	254	0.5	4	132	2
15610305	0.01	305	0.3	4	158	2.41



HYDROSCAND