

EXHAUST HOSE FOR HOT AIR, SILICONE, DOUBLE COATED



Product group	140
Cover design	Slightly corrugated
Color	Red
Bundled pipes/hoses	1
Media description	Ventilation
Antstatic wire	No
Cover tube material	Silicon
Flat coil	No
Inner tube material	Silicon
Max temperature (°C)	300
Reinforcement layers	1
Reinforcement mtrl	Steel spiral
Min temperature (°C)	-50

A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length metre per coil	Weight (kg)
15621016	18	0.28	25	7	4	1
15621020	20	0.26	32	6	4	0.17
15621029	27	0.26	44	5	4	1
15621032	31	0.26	51	5	4	0.29
15621040	37	0.24	63	5	4	0.36
15621048	43	0.21	76	4	4	0.46
15621055	50	0.2	89	4	4	0.53
15621064	56	0.19	102	3	4	0.6
15621080	70	0.14	127	3	4	0.86
15621096	82	0.12	152	2	4	1.1
15621180	95	0.1	180	1	4	1.28
15621203	108	0.07	203	1	4	1.43

