

Polyurethane hose HD T 2.0



Product group	140
Cover design	Corrugated
Bundled pipes/hoses	1
Media description	Materials
Cover tube material	PUR
Flat coil	No
Inner tube material	PUR
Antstatic wire	No
Max temperature (°C)	90
Reinforcement layers	No extra reinforcement
Reinforcement mtrls	Steel wire
Min temperature (°C)	-40

An extremely powerful PU-hose for both suction and pressure transports of abrasive materials such as sand, granulates and splinters. The hose is suitable in the contractor business area, the wood and plastic industries.

Part no	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length metre per coil	OD (mm)	Bend radius (mm)	Weight (kg)
15637025	0.43	40	94	10	50	100	0.76
15637032	0.4	51	94	10	61	125	1
15637038	0.38	55	89	10	65	140	1.1
15637039	0.36	60	89	10	70	150	1.32
15637048	0.29	76	89	10	87	190	1.51
15637056	0.24	90	89	10	103	225	1.81
15637064	0.21	102	87	10	115	250	2.13
15637070	0.2	110	87	10	124	275	2.82
15637096	0.15	152	82	10	167	450	4.08
15637160	0.14	160	81	10	175	500	4.81
15637170	0.12	170	80	10	185	600	5.1
15637200	0.1	200	0.85	10	217	800	6.43
15637203	0.11	203	66	10	220	950	6.43
15637250	0.09	250	51	10	267	1,300	7.91
15637300	0.06	300	42	10	317	1,600	9.45

