Metal hose, parallel wrapped



Safety factor	1:4
Antstatic wire	No
Flat coil	No
Max temperature (°C)	550
Reinforcement mtrls	Stainless steel (1.4301)
Min temperature (°C)	-200

Metal hose suitable for hot oils, chemicals, gases, exhaust gases, water, steam, vacuum etc. The hose can also be used as mechanical cable protection. Inner tube: Stainless steel (1.4541 EN 10088-1) Suffix F Stainless steel (1.4404 EN 10088-1) Suffix S

Part no	ID (mm)	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
14840106S	10.6	17.5	190	7.5	0.24
14840108F	12.3	19.5	210	7	0.29
14840110F	15.7	25.2	285	6.5	0.37
14840110S	15.7	25.2	285	6.5	0.4
14840112F	19.8	30.3	310	5	0.52
14840116F	25.8	36	375	4	0.66
14840116S	25.8	36	375	4	0.66
14840120F	33	45.7	405	3.5	1
14840124S	40	54	480	3	1.16
14840140S	66	87.9	675	2	2.47
14840148F	76.6	100	750	1.8	2.89
14840164F	103	128	920	1.4	4.14
14840180F	127.5	154.5	1,160	1.25	5.83
14840180S	127.5	154.5	1,160	1.25	5.77

