

AQUASEWER, FLUSHING HOSE THERMOPLAST, 250 BAR



Product group	140
Color	Red
Cover design	Smooth
Media description	Water
Safety factor	1:2.5
Bundled pipes/hoses	1
Cover tube material	PU
Flat coil	No
Inner tube material	PE
Antstatic wire	No
Max temperature (°C)	60
Reinforcement layers	2
Reinforcement mtrls	Nylon
Min temperature (°C)	-40

A hose suitable for high pressure sewage systems. The hose has low weight compared to rubber hoses, which leads to less abrasion and increased flowing speed. The hose sustains 3–4 times more external abrasion compared to a traditional rubber hose. It is delivered pre-assembled with fittings according to demand. Delivered with Pressure Test Certificate.

Part no	ID (mm)	Length metre per coil	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
14190608	13	60	22.8	75	25	0.29
14190612	19.6	60	30.3	120	25	0.49
14190616	25.9	60	37.9	155	25	0.62
14190812	19.6	80	30.3	120	25	0.49
14190816	25.9	80	37.9	155	25	0.62
14191208	13	120	22.8	75	25	0.29
14191212	19.6	120	30.3	120	25	0.49
14191220	32.4	120	45.3	240	25	0.74
14191512	19.6	150	30.3	120	25	0.49
14191516	25.9	150	37.9	155	25	0.58

