


## LIFTING SHACKLE USAL

8130-24



<b>Product info</b>	For permanent connection.
<b>Product info2</b>	Forged, straight shackle with spesification US RR-C-271. Delivered galvanized with painted screws - red pin - in straight design. Labeling: Maximum load.
<b>Type</b>	Lifting products
<b>Safety factor</b>	6:1
<b>Product group</b>	505

Part no.	Dimension mm A	Dimension mm B	Dimension mm C	Dimension mm D	
81302435	35,0	52,0	119,0	32,0	12,00
81302419	19,0	27,0	64,0	16,0	3,25
81302432	32,0	46,0	108,0	29,0	9,50
81302410	10,0	13,0	32,0	9,0	0,75
81302451	51,0	73,0	178,0	44,0	25,00
81302438	38,0	57,0	133,0	35,0	13,50
81302429	29,0	43,0	95,0	25,0	8,50
81302408	8,0	12,0	29,0	7,0	0,50
81302413	13,0	18,0	43,0	11,0	1,50
81302416	16,0	21,0	48,0	13,0	2,00
81302422	22,0	32,0	71,0	19,0	4,75
81302411	11,0	16,0	36,0	10,0	1,00
81302425	25,0	36,0	84,0	22,0	6,50
81302441	41,0	60,0	146,0	38,0	17,00